

Ethylene Propylene Diene Terpolymer

KUMHO POLYCHEM

Product Data Sheet

Product Description		Features	
KEP281F is an EPDM rubber with broad molecular weight distribution, high ethylene , medium ENB contents. It can be used to weather strip solid, Heat-resistance hose, window seals and Various type of automobile parts.		<ul style="list-style-type: none">- High Mooney Viscosity/ high loadability- High curing speed- Improved productivity & Collapse resistance- Characteristics suitable for weather strip	
Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 0.75	wt %	ASTM D5668
Mooney Viscosity ML(1+8)@125 °C	82.0 ± 5.0	MU	ASTM D1646
Ethylene Contents	67.0 ± 3.0	wt %	ASTM D3900
ENB Contents	5.7 ± 1.0	wt %	ASTM D6047

Other Products Features

Product Form	Bale
Packaging	25 kg/Bag in Mesh/Carton/MB5 Box, LDPE film, 900 kg (25 kg × 36)
Shelf Life	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
The Others	RoHS Free

Contact Information

Head Office	East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-1114
Plant	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2821
Revision Date	05/09/2025
Revision No.	13