

Ethylene Propylene Diene Terpolymer

KUMHO POLYCHEM

Product Data Sheet

Product Description		Features	
KEP350 is an EPDM rubber with Medium molecular weight distribution, low ethylene, high ENB. It can be used to Cover strips, white sidewalls, window seals, gaskets, packing, and sponge.		<ul style="list-style-type: none">- Low Mooney viscosity with excellent Processability- Ultra fast vulcanization- Suitable for blends with diene type rubbers	
Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 0.75	wt %	ASTM D5668
Mooney Viscosity ML(1+4)@125 °C	56.0 ± 6.0	MU	ASTM D1646
Ethylene Contents	56.5 ± 3.5	wt %	ASTM D3900
ENB Contents	7.9 ± 1.0	wt %	ASTM D6047
Other Products Features			
Product Form	Bale		
Packaging	25 kg/Bag in Mesh Box, LDPE film, 900 kg (25 kg × 36)		
Shelf Life	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided		
The Others	RoHS Free		
Contact Information			
Head Office	East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-1114		
Plant	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2821		
Revision Date	01/11/2025		
Revision No.	7		